Power supply PEDESTALS **Sourcelec ESCALE 156**



Sourcelec pedestal designed for Marinas. It enables simultaneous supply of electricity and water.



Features

- Equipment made of fiberglass-reinforced polyester with integrated isophtalic gel coat surfacing, self-extinguishing at 850°C.
- Protection degree : IP 44 IK 10. High resistance to UV, infrared, external aggressions and humidity.
- Standard colour: white (other colours on request).

Closing and fixing devices

- · Door fitted on hinged stainless steel hinges.
- Locking by 2 1/4 turn, burglar-proof and stainless locks.
- 4 fixing points, spacing: 100X280 mm.

Options (on estimate)

- Customizing with your logo, graphic design, texture, colour...
- Blue colour LED.
- Padlockable socket.

Standards

Complying with NF C 15-100 standard, section 709, 2002 edition : Low Voltage electrical installations for Marinas.

Dimensions in mm


Ergonomics


- Low depth for the best on-site integration
- 4 sockets and 4 water outlets maximum
- Side location of the pedestal

Lighting & Markings

Energy saving:

- · Consumption: Supply:
- 4W / Lampled
- Integrated 230Vac for Lampled
- 0.3W / Spotlight - 12V for Spotlight





White Sourcelec ESCALE 156 pedestal	Depagne
Which can be fitted electricity/water	415 608 00

Standard equi	pment	Depagne
Kit for 1 socket 2P+E 16A IP44 with Ph+N 16A with RCD circuit breaker 30mA, ready assembled		941 110 00
	1 tap ¼ turn	943 101 00
	1 quick coupling	943 201 00

^{*} For all our references, refer to the documentations : 21749-16 and 21750-16.

Lighting and Markings		Depagne
Kit with 1 Lampled 230V, with protection, ready assembled		920 006 00
Marking kit with 12V supply and protection, ready assembled	2 Spotlights	920 211 00
	4 Spotlights	920 411 00



